



# ACOUSLIME

## 3 in 1 Features

- ✓ High elastic strength timber flooring adhesive
- ✓ Moisture vapour barrier - Adhesive is waterproof when cured
- ✓ Allows normal dimensional changes





## Installation Features

- Contains a moisture vapour barrier
- One step process
- Saves time & money
- Ready to use - no mixing required
- Wet lay – no flash time needed
- Easy trowelling with smooth consistency
- Low viscosity
- High filling capacity
- Excellent ridge holding
- Strong green grab
- Reduces stress on subfloor
- Elastic
- Bridges normal sub floor variations
- No dimensional changes in timber flooring
- Bonds all wood types
- Low odour
- Clean up with damp watery cloth (pH Neutral) whilst still wet or peel off when dry
- 4mm V Notch Trowel required to achieve moisture barrier
- Coverage approx. 14m2 dependant on substrate

## Approved Sub Floors

- Concrete Slabs
- Subfloor heating without primer
- Cured levelling compounds
- Existing timber flooring
- Particleboard & chipboard
- Plywood
- Ceramic Tiles
- Marble



## General Features

- SMP – Silane Modified Polymer
- Moisture vapour barrier and timber stabiliser
- Contains no isocyanates
- Contains no solvents Certified DIN EN 13556 compliant (European standard for flooring adhesives)
- Very low emission
- Available in 600ml sausages and 16kg tubs
- Suitable for solid timber, engineered timber and parquetry - install to manufacturer's instructions and adhere to ATFA industry standards

